

## 2022 GUT and GO COMPACT RULES

**Participants Regulations:** Bone stock class is open to all men and women 16 and over, if under the age of 18 you must have a notarized permit signed by a parent/guardian.

Driver may move forward or backward. Driver must make contact every 60 seconds or be disqualified. No sandbagging. You must show visible damage or must move when hit.

**DRIVER RULES** Drivers and passengers must be at least 18 years of age or if 16 or 17 years of age must have notarized permit by parent/guardian. Driver must furnish his/her own car. If this is a passenger heat all drivers, passengers and pit persons must sign a waiver of release of liability before entering pit area or track. IF YOU ARE NOT IN LINE TO BE CHECKED IN AT LEAST AN HOUR BEFORE START TIME YOU WILL BE CHARGED AN EXTRA \$20.00. All driver and pit people must attend meeting prior to race time.

**MANDATORY PASSENGER RULES** Must at least have a secure 4 point cage approved by officials for driver and passenger safety. Must have a t- handle or something similar to hold onto. Seat must be bolted down in stock position. Must have a seat belt. Must have sufficient amount of padding to protect the rider. If you do not have the items you will not be able to run passengers. NO EXCEPTIONS!!!!

**Preparation of cars:** Front wheel drive or rear wheel drive cars no 4x4's and no pacers, wheel base not to exceed 106 inches from center of wheel to center of wheel (must be factory 106 inches cannot move wheels in) All glass, chrome, pot metal, head lights, tail lights, back seats. Anything flammable must be removed.

### **THE RULES BELOW ARE THE ABSOLUTE MAX YOU MAY DO TO A CAR .**

1. Dash may be removed.
2. Cars need to be 4 or 6 Cylinders only.
3. Stock gas tank can be used under car if it's in front of the rear axle. If, changed to inside it must be a metal fuel cell no exceptions. Must be secured properly with no movement and no fuel leakage. No more than 6 gallons gas.
4. Battery may be relocated to inside of car but must be secured properly (1 automotive battery)
5. Hood must have a 5x5 hole cut in it to extinguish fires. Hood must open for inspection and must remain on hinges. You can use 8 pieces of 3/8 chain. 6 in hood to fender, 2 from hood to bumper or you can use 9 wire the same way with 3 wraps per fastening spot. Must have windshield bar from top of windshield to top of fire wall you can use 9 wire, chain or 3 inch flat metal. 2 max in this area.
6. Trunks must be on hinges. You can use 8 pieces of 3/8 chain in trunk 6 to fasten trunk lid and 2 from trunk lid to bumper. Or you can use 9 wire the same way with 3 wraps per fastening spot. You can tuck 50% of trunk lid only or remove trunk lid completely.

7. BUMPERS. Must use stock factory bumper from a compact car. If it has a plastic bumper you may replace it with a 1 piece style bumper. It can be bolted on with factory bolts or two  $\frac{3}{4}$  x 8 inch all thread 1 per frame rail with 3 inch washers.. As stated in rule 5 you can also use nine wire or chain along with bolting.

8. Doors you can use 6 pieces of  $\frac{3}{8}$  chain per door or 6 pieces of 9 wire per door with 3 wraps. Both front doors you can have a six inch wide piece of channel or equivalent from 6 inches in front of front doors to 6 inches behind front doors. May be welded or bolted. May have bar behind front seat no further back than 3 inches behind front seat.

9. TIRES: D.O.T. approved light truck tires max.

10. NO HEADER PIPES.

11. REAR ENDS: Locking of rear ends permitted.

12. FRAME Notching of frame permitted but cannot be welded back together.

13. THIS IS THE MAX OF WHAT YOU CAN DO ON A BONE STOCK CAR. DO NOT DO ANYMORE THAN THIS OR YOU WON'T BE RUNNING THIS CLASS.